



# AUTOMATIC TRANSMISSION FLUID



## TDS

### ATF VI

#### PRODUCT DESCRIPTION

PONTE MILANO automatic transmission fluid (ATF VI) is recommended for all automatic transmission and hydraulic systems. It provides outstanding performance in automatic transmissions and power steering units. Special base stocks in combination with a modern additive technology provides its constant friction characteristics, wide operating temperature range, high shear stability, excellent anti-wear properties ensuring long transmission life and consistent smooth shifting over its whole service period.

#### PROPERTIES

FEATURES	BENEFITS
Excellent frictional characteristics giving smooth transmission operation.	Increased oil life and protection against deposit formation.
Compatibility with seal materials.	Guarantees oil performance over time

#### SPECIFICATIONS

PONTE MILANO ATF III has been developed to meet the highest international standards, including:

Test	Result	Standard
Visual appearance	Clear	-----
Viscosity index	151	
Viscosity @ 100°C (cSt)	27.16	ASTM D-445
Brookfield Viscosity @ -40 °C, cP	11400	ASTM D-2983
Viscosity @ 40 °C	5.6	ASTM D-2270
Pour Point, °C	-30	ASTM D-97
Flash Point, °C	213	ASTM D-92
Fire Point, °C	225	

All products may not be available locally. For more information, contact your distributor or visit [www.ptk-holding.com](http://www.ptk-holding.com) due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2017 PONTE MILANO. All rights reserved. This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.