



TDS

API CH4 20W-50

PRODUCT DESCRIPTION

PONTE MILANO CH4 20W-50 is a synthetic technology oil that offers outstanding performance of the modern Diesel engines as well as older models. This product guarantees outstanding performance and exceeds the prevailing engine OEM manufacturers requirements by using high quality base oil and exclusive additives. PONTE MILANO suggests PONTE MILANO CH4 20W50 maximum engine power and high fluidity lubricant is required in normal or high temperature condition.

PONTE CH4 20W-50 is formulated from high quality bases combined with modern performance additives to provide with exceptional features.

PROPERTIES SPECIFICATIONS

PONTE CH4 20W-50 has been developed to meet the highest international standards.

Property	Value	Test Method
SAE	20W-50	
API	CH4	
Viscosity @ 40°C (cst)	166.37 mm ² /s	ASTM D-445
Viscosity @ 100°C (cSt)	19.88 mm ² /s	ASTM D-445
Viscosity Index	137	ASTM D-2270
Pour Point, °C	- 33 C	ASTM D-97
Flash Point, °C	224 C	ASTM D-92
Density @ 15.5°C (g/cm ²)	0.8864	ASTM D-4052
Noack	9.8	ASTM D-5800
CCS-cp@-20 °	3359	ASTM D-5293

PONTE CH4 20W-50 has been mainly developed to answer the needs of demanding applications, such as heavy vehicles. Because this product was born on the track.

All products may not be available locally. For more information, contact your distributor or visit www.pontemilano.it Due to continual and extensive product Research and Development, the information contained herein is subject to change without notification. Typical properties may vary slightly, but not significantly.

© 2014 PONTE. All rights reserved.